FLASHTOASTER FOR READING SEVERAL TYPES OF FLASH MEMORY CARDS WITH OR WITHOUT A PC

Publication number: WO0205102

Publication date:

2002-01-17

Inventor:

JONES LARRY LAWSON; MAMBAKKAM SREENATH;

AROCKIYASWAMY VENKIDU ONSPEC ELECTRONIC INC (US)

Applicant: Classification:

- International:

G06K19/077; G06F13/38; G06K7/00; G06K17/00; G06K19/077; G06F13/38; G06K7/00; G06K17/00;

(IPC1-7): G06F13/00

- European:

G06F13/38; G06F13/38A2; G06K7/00K

Application number: WO2001US41249 20010703 Priority number(s): US2000610904 20000706

Also published as:

ENERGY

US7222205 (B2) US6832281 (B2) US6438638 (B1) US2003084221 (A1) US2003041203 (A1)

more >>

Cited documents:




. US6264506 US6075706

Report a data error here.

Abstract of WO0205102

A flash-memory-card reader (42) reads and writes multiple types of flash-memory cards (16, 18, 24, 28, 26), including CompactFlash (16), and the smaller SmartMedia (24), MultiMediaCard (28), Secure Digital (26), and Memory Stick (18). A converter chip (40) converts the different card signals for transfer to a host personal computer. (PC) (20). Serial-to-parallel data conversion is performed for the smaller card formats with serial data interfaces, but not for CompactFlash with a parallel-data interface. A single slot (22) has a 50-pin connector for CompactFlash cards (16) or passive adapters (30, 32 34). The passive adapters have the CompactFlash (16, 28, 24, 18) form factor and a smaller connector fitting smaller. flash cards (30, 34, 32). Passive adapters have no components but simply wire the smaller. connector to the CompactFlash connector (62, 64, 66, 68). A pin mapping allows card-type detection by sensing the LSB address pins of the CompactFlash interface. A larger CompactFlash reader (42) has multiple slots (44) for each card type. The reader (42) is connected to the PC by a cable (46), or located within the PC chassis in a drive bay. A stand-alone reader (42) copies images from the flash-memory card (16) to a removable disk media. Pressing a button initiates image transfer.



Data supplied from the esp@cenet database - Worldwide